

SRE 229 E HEATER



Product data sheet

Product range	Portable heaters
Product line	Laser
Brand name	Zibro
Model name	SRE229E
Colour	Dark grey metallic
EAN code Black	8713508753768

Technical specifications

Burner type	Electronic Injection Burning System (BI)	
Capacity	kW	0.8 - 3.2
Suitable space	m ²	16 - 48
	m ³	40 - 120
Fuel consumption	ltr/hr	0.083 - 0.333
	g/hr	67 - 267
Tank capacity	ltr	5.4
Autonomy	hr	16.7 - 65.0
Mains	V / Hz	230 / 50
Power consumption	W	320
Power consumption burning	W	13
Noise level (low-high)	dB(A)	18 - 35
Dimensions (w x d x h) *	mm	376 x 296 x 428
Weight	kg	8.0
Guarantee	years	4

* including base plate


Accessories

Instructions for use


Manual fuel pump

Most important spare parts

Description	Model	EAN Code
Removable fuel tank	K	8713508750804
Fuel tank cap	tbc	tbc
Fuel filter	tbc	tbc
Mica window	tbc	tbc
Burner mat	I	8713508758145



20 ft = 360
40 ft = 752
HQ = 940



W x D x H =
428 x 340 x
485 mm



Gross =
10.0 kg

zibro®

home made climates

SRE 229 E HEATER



E-Guard




Automatic tip-over switch



Improved save mode
(+8%)



Day timer



Fuzzy Logic



Mode booster



Freezing prevention

Features

Fuzzy logic: This heater is equipped with a self-regulating temperature control system. The heating mode can be set according to the requirements.

Semi-automatic operation: This heater is equipped with a 24-hour programmable timer and integrated thermostatic control to maintain the desired room temperature.

Wickless design: Provides clean and economical heating without wick maintenance or replacement.

New Save mode: The 'SAVE' function allows you to remain the set temperature in the room. This saves up to 8% on the energy consumption.

Automatic cleaning mode: When the heater has been burning for two hours consecutively at its maximum burning mode it will automatically clean the burner chamber for a period of 5 minutes.

Information display: Helps to keep track of all the important heater functions.

Safety devices: This heater is equipped with a combustion quality sensor, an over-heat protector, a tip-over switch and a burner thermistor for safe heating.

Safety system: This heater is fitted with a safety system that automatically switches off the heater after approximately 65 hours of continuous operation.

Childproof lock: When this button is pressed, the operation of buttons will be blocked, except the on/off button.

Clean grip fuel tank cap: A new way to unscrew the removable fuel tank cap without touching the tank directly.

Automatic airflow control: The speed of the built-in fan is self-regulatory, depending on the burning mode of the heater.

Additional high burning mode: This feature is also known as booster. It provides 10% extra heating capacity for 5 minutes, in addition to the heat output in the maximum burning mode during a cold start (room temperature below 10°C and set temperature above 15°C).

Air quality control system (E-Guard): This heater is equipped with a E-Guard air quality control system. The customer is informed when additional ventilation is required. The heater will be switched off when the room is not ventilated sufficiently.

Made in Japan: This heater has been produced according to the ISO 9000:2000 Quality Control Standard.

Quiet operation: When heating the room, the device produces only a limited amount of sound.

High altitude setting: For use at higher altitudes, the settings of the heater can be adapted to the situation.
